


N Straight Jack (1/2" R)

53K1C7-C03N1



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

IEC 60169-16, MIL-PRF-39012, CECC22210

Documents

Assembly instruction

MA_1C7-C03(In package)

Material and plating

Connector parts

Center contact
Outer contact
Body
Dielectric
Gasket

Material

Spring bronze
Brass
Brass
TPX
Silicone

Plating

Silver, 3-6 μ m
Flash white bronze over silver(e.g. Optargen®)
Nickel, 2.5-5 μ m

TECHNICAL DATA SHEET

Rosenberger
Rosenberger Site Solutions, LLC

N Straight Jack (1/2" R)

53K1C7-C03N1

Electrical data

Impedance	50 Ω
Frequency	DC to 11GHz
Return loss	≤ -35dB, DC to 1 GHz
	≤ -32dB, 1 to 2.7 GHz
Insertion loss	≤ 0.1 dB
Insulation resistance	≥ 5x10 ³ MΩ
Center contact resistance	≤ 1mΩ
Outer contact resistance	≤ 0.25mΩ
Test voltage	2500 V rms
Working voltage	1400 V rms
Power handling (at 20 °C, sea level, VSWR 1.0)	1000 W @ 1 GHz
	700 W @ 4 GHz
Intermodulation (3 rd order)	≤ -117dBm @ 2 x 20 W
- Limitations are possible due to the used cable type	

Mechanical data

Mating cycles	min. 500
Center contact captivation: axial	≥ 28 N
radial	≥ 3 Ncm
Coupling test torque	max. 1.7 Nm
Recommended torque	0.7 Nm to 1.1 Nm

Environmental data

Temperature range	-45°C to +85°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. B
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture resistance	MIL-STD-202, Meth. 106
Degree of protection (mated pair)	IEC 60529, IP68
2002/95/EC (RoHS)	compliant

Tooling

60W110-C03

Suitable cables

SL 012R series (Recommend)

Packing

Standard	1pce in box
Weight	64.6g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Checker	Approved	Date	Rev.	Engineering change number	Name	Date
Roger	ZhaiQK	Marshall	12/05/09	b	09-0337	Roger	12/05/09
Corporate Headquarters Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O. Box 1260 D-84526 Tittmoning Germany Tel. +49 8684 18-0				Rosenberger Site Solutions, LLC P.O. Box 4268, Lake Charles, LA 70606 Ph.337.598.5250 Fax: 337.598.5290 rlss@rlss.us www.rlss.us			Page 2 of 2