Installation Instructions



TH Series Stainless Steel Hardware

This general installation instruction applies to all Rosenberger TH series Stainless Steel Threaded Rod Kits.

Typical Application

These threaded rod kits allow Hanger Clamps, and Mini and Large Coax Support Blocks to be easily and quickly stacked in 1, 2, and 3-stack configurations and then mounted to pre-drilled holes or used in conjunction with a complete selection of mounting accessories. Include pre-cut threaded rods, nuts, flat washers, and lock washers. Please verify the torque used at installation is approproate for the application.



Stainless Steel Rod Kit - Each Contains: 10 Threaded Rods, 20 Flat washers, 20 Lock washers & 30 Nuts

		Stack Height (# of Hangers) by Cable Type					
Part #	Description	3/8	1/2	7/8	1-1/4	1-5/8	2-1/4
TH475-CH383S	Stainless Steel Rod Kit 3/8" x 3.75	1	1	1			
TH475-CH384S	Stainless Steel Rod Kit 3/8" x 4.25	2	2	2	1		
TH477-CH386S	Stainless Steel Rod Kit 3/8" x 6.25	3	3	3		1	1
TH478-CH388S	Stainless Steel Rod Kit 3/8" x 8				2	2	
TH479-CH3810S	Stainless Steel Rod Kit 3/8" x 9.5				3	3	2
TH480-CH3812S	Stainless Steel Rod Kit 3/8" x 12						3

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.

NOTE

Installation of this product should only be performed by trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly before installation is performed. The manufacturer and supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.