

PLASTIC THREE WAY STAND-OFF ADAPTER BLOCK KIT TH502-SA14

PLASTIC THREE WAY STAND-OFF ADAPTER WITH PLASTIC ROUND MEMBER
ADAPTER 1/2" TO 4" . INCLUDES (10) THCO-PW100 AND (1) TH501-SA38



General Specifications (THCO-PW100)

Material	PA 12 - 20 Year Weatherable
Diameter Range	0.5-3.9 inches (13-100 mm)
Length	14.2 inches (360.1 mm)
Band Width	0.5 inches (12.7 mm)
Hex Screw	0.315 inch (8 mm)
Max Torque	22 in/lb (2.5 Nm)
Operating Temperature Range	-40 to +85 Degrees C Melting Point: 178 Degrees C



Material Property	Standard	Value
Tensile Strength	Telcodia	250 lbs (1,112 kg)
Flame Resistance	UL-94	HB
Tensile Modulus	ISO 527	1600 MPa
Flexural Strength	ISO 178	60 MPa
RoHS Compliant		

General Specifications (TH501-SA38)

Length	97.16 mm 3.8 in
Width	42.00 mm 1.65 in
Height	40.00 mm 1.57 in
Hole Size, Quantity	3/4", Three (for Snap-ins)
Material Type	Nylon 6



Package Quantity One Kit with (10) THCO-PW100 (1) TH501-SA38

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.

NOTE

Installation of this product should only be performed by trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly before installation is performed. The manufacturer and supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.