


Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/05.10/6.0

Technical Data Sheet

4.3-10
Calibration Kit
Jack

64K36R-MSOS3



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 61169-54

Documents

N/A

Material and plating

Connector parts

- Center conductor
- Outer conductor
- Body
- Dielectric
- Substrate

Material

- CuBe
- Stainless steel
- Brass
- PTFE
- Al₂O₃

Plating

- Gold, min. 1.27 µm, over nickel
- Passivated
- White bronze(e.g. Optalloy®); powder-coated

4.3-10

Calibration Kit
Jack

64K36R-MSOS3

Electrical data

Frequency range DC to 6 GHz

Open

Return loss ≤ 0.15 dB, DC to 6 GHz

Error from nominal phase¹ $\leq 3.0^\circ$, DC to 6 GHz

Short

Return loss ≤ 0.15 dB, DC to 6 GHz

Error from nominal phase² $\leq 2.0^\circ$, DC to 6 GHz

Load

Return loss ≥ 40 dB, DC to 2.5 GHz

≥ 38 dB, 2.5 GHz to 6 GHz

DC-Resistance $50 \Omega \pm 0.5 \Omega$

Power handling ≤ 1.0 W

¹ The nominal phase is defined by the Offset Delay, the Offset Loss and the Fringing Capacitances

² The nominal phase is defined by the Offset Delay, the Offset Loss and the Short Inductance

Mechanical data

Mating cycles ≥ 100

Maximum torque 5 Nm

Recommended torque 2 Nm

Gauge 3.10 mm to 3.25 mm

General standard definitions

For proper operation the vector network analyzer (VNA) needs a model describing the electrical behaviour of this calibration standard. The different models, units, and terms used will depend on the VNA type and they will have to be entered into the VNA. All values are based on typical geometry and plating.

Open

Offset Z_0 / Impedance / Z_0 50 Ω

Offset Delay 66.946 ps

Length (electrical) / Offset Length 20.07 mm

Offset Loss 0.70 G Ω /s

Loss 0.0081 dB/ $\sqrt{\text{GHz}}$

Fringing Capacitances $C_0 = 1.48800 \times 10^{-15}$ F / 1.48800 fF

$C_1 = -3105.90 \times 10^{-27}$ F/Hz / -3.10590 fF /GHz

$C_2 = 673.380 \times 10^{-36}$ F/Hz² / 0.67338 fF /GHz²

$C_3 = -37.8300 \times 10^{-45}$ F/Hz³ / -0.03783 fF /GHz³

Technical Data Sheet

4.3-10

Calibration Kit
Jack

64K36R-MSOS3

Short

Offset Z_0 / Impedance / Z_0	50 Ω		
Offset Delay	66.946 ps		
Length (electrical) / Offset Length	20.07 mm		
Offset Loss	0.70 G Ω /s		
Loss	0.0081 dB/ $\sqrt{\text{GHz}}$		
Short Inductance	$L_0 = 0.0000 \times 10^{-12}$ H	/	0.0000 pH
	$L_1 = 0.0000 \times 10^{-24}$ H/Hz	/	0.0000 pH/GHz
	$L_2 = 0.0000 \times 10^{-33}$ H/Hz ²	/	0.0000 pH/GHz ²
	$L_3 = 0.0000 \times 10^{-42}$ H/Hz ³	/	0.0000 pH/GHz ³

Load

Offset Z_0 / Impedance / Z_0	50 Ω
Offset Delay	0.0000 ps
Length (electrical) / Offset Length	0.000 mm
Offset Loss	0.00 G Ω /s
Loss	0.0000 dB/ $\sqrt{\text{GHz}}$

Environmental data

Operating temperature range ³	0 °C to +50 °C
Storage temperature range	-55 °C to +90 °C
RoHS	compliant

³Temperature range over which these specifications are valid.

Packing

Standard	1 pce in bag
Weight	203 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	01/10/13	Markus Müller	14/08/14	b00	14-1131	Marion Striegler	14/08/14
Corporate Headquarters Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O. Box 1260 D-84526 Tittmoning Germany Tel. +49 8684 18-0				Rosenberger Site Solutions, LLC P.O. Box 4268, Lake Charles, LA 70606 Ph.337.598.5250 Fax: 337.598.5290 rlss@rlss.us www.rlss.us			Page 3 of 3