Technical Data Sheet		Rosenberger Site Solutions	
1- 5/8" Hang	er Grommet	CX614-155	
		Ø 55.50	
Hanger Grommet with one 34x for 1-5/8" Hangers and 1-5/8" I When installed properly, this prod installation in High Risk PIM Zone this product must be used in conj Zone approved products.	Double Clamps. uct meets the requirements for s. For use in High Risk PIM Zones,		
General Specifications		Note	
Туре:	Single-hole Grommet	Installation of this product should only be perform	ned by
Cables per Grommet:	1 (one)	trained, qualified and experienced personnel. Insta	
Dimmensions:	. (0.00)	instructions for this product should be read thorous	
	50.00	before installation is performed. The manufacturen supplier of this product disclaims any liability or	ailü
Height:	56.00 mm [2.204 in]	responsibility for the results of improper or unsafe	9
Hole Shape:	Oval	installation practice.	
Cable Hole size:	34x37 mm [1.338 - 1.456 in]	-	
			_
Material Specifications		Compatible Rosenberger Hardware	
Material Type:	Rubber	1-5/8" Universal Hanger: TH415-U158 1-5/8" Snap-Stack Hanger: TH428-S158	
Standards:	ASTM-1148-07a Unaffected by ozone, sunlight, aging or hot and cold weather. RoHS Compliant	1-5/8" Double Clamp: TH497-DC158 1-5/8" SIC Clamp: CX-SIC4-158	
Packaging			
Packaging quantity:	10 pcs		
Packaging quantity. Weight Per Package	1.08 kg [2.4 lb]		
orporate Headquarters osenberger Hochfrequenztechnik Gr .O. Box 1260 D-84526 Tittmoning Go			e: 1/1

Ver: 201113.NR.v1.0