



## NOTES

part, for any purpose without the prior written consent of Sabre.

© 2006 Sabre Communications Corporation.

All rights reserved.

- THE ABOVE LIST OF MATERIAL CONTAINS MATERIAL FOR ONE ANCHOR ONLY.
- 2. IT IS THE OWNERS RESPONSIBILITY TO ENSURE THAT THE CONNECTION TO THE ROOF IS ADEQUATE TO SUPPORT THE REACTIONS SHOWN ON THE TOWER ERECTION DRAWING.
- AFTER TIGHTENING THE 1" BOLT TO THE CORRECT TORQUE, STAKE THE THREADS TO PREVENT LOOSENING OF NUT.

ISOMETRIC VIEW

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES

TOLERANCES: FRACTIONS ± 1/16" ANGLES ± 1/2 DEG. DECIMALS ± .010"

TOLERANCES DO NOT APPLY TO RAW MATERIAL

CONFIDENTIAL

This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in

DESCRIPTION

ROOF MOUNTED ANCHOR INSTALLATION
(3/8" EHS MAX.)

|            |          | SIZE | DRAWING NO. |       |      | REV  |
|------------|----------|------|-------------|-------|------|------|
| DATE       | 05/21/04 | В    | C30904301   |       |      | 0    |
| DRAWN BY   | WRF      | •    |             | SCALE | PAGE |      |
| CHECKED BY | DLW      | 1    |             | None  |      | 0F 1 |