Product Specifications



LOW PIM ROLLS OF DELRIN® ACETAL STRAPPING TX-AR50F10E

50' PLASTIC REEL OF ACETAL (DELRIN®) STRAP FOR USE IN ATTACHING PLASTIC STANDOFFS AND HANGER ADAPTER GROMMETS TO ROUND MEMEBERS IN HIGH RISK PIM ZONES



General Specifications

MaterialAcetal PlasticTensile Strength (lbs./ kg)400/180Body Width (in./mm)0.50/12.70Thickness (in./mm)0.052 / 1.32Length50 FTBellcore / TelcordiaApproved

Packaging

Package Quantity

Related Products

Part Number	Description	U of M
TX-AH25E	ACETAL LOCKING HEAD FOR DELRIN TIES	Pack of 25
TX-T3DY	BLUE TENSIONER TOOL FOR DELRIN TIES	Each

1 reel

NOTE

Installation of this product should only be performed by trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly before installation is performed. The manufacturer and supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.

Phone: (337)598-5250 Fax: (337) 598-5290 Web: www.RosenbergerOnline.us Version 051719