


Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/05.10/6.0

Technical Data Sheet		Rosenberger
1/2" JUMPER	7-16 R/A MALE / 4.3-10 MALE	SLJ12SP-60R64M-X-00
		
Function Description		
This part is a coaxial cable assembly for telecommunication equipment. It consists of 1/2" super flexible coaxial cable with PE jacket, one 7-16 right angle connector and one 4.3-10 male connector. The assembly is waterproof in mated condition and UV protected.		
Available Variants		
The assembly is available in lengths from 0.5 m to 10 m in intervals of 0.5 m. Different feet length are available on request.		
Assembly Parts		
Connector	7-16 r/a male and 4.3-10 male (screw-type) connector plated with white bronze	
Cable	S-Link 1/2"S, PE jacket	
Marking 1	Direct print onto the cable or one wrapping label Marking includes manufacturer, part nr. & batch no.	
Marking 2	Direct print onto the cable or on wrapping label Marking includes "Rosenberger factory made" Position in the middle of the cable	
Bend Protection	molding material TPE compound	
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de		Tel. : +49 8684 18-0 Email : info@rosenberger.de Page 1 / 2

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/05.10/6.0

Technical Data Sheet				Rosenberger			
1/2" JUMPER		7-16 R/A MALE / 4.3-10 MALE		SLJ12SP-60R64M-X-00			
Electrical Data Impedance Frequency Return loss DC – 1 GHz 1 – 2.2 GHz 2.2 – 2.7 GHz Insertion loss typ. DC – 1 GHz 1 – 2.2 GHz 2.2 – 2.7 GHz Intermodulation (3rd order @ 2 x 20 W) Relative Velocity of Propagation DC breakdown voltage 50 Ω DC to 2.7 GHz ≥ 32 dB ≥ 30 dB ≥ 28 dB ≤ 0.12 dB/m (cable) + 0.01 dB * √f (GHz) ≤ 0.18 dB/m (cable) + 0.01 dB * √f (GHz) ≤ 0.20 dB/m (cable) + 0.01 dB * √f (GHz) typ. max. ≤ -120 dBm ≤ -117 dBm 83 % 2500 V							
Mechanical Data Coupling torque 7-16 (recommended) Coupling torque 4.3-10 (recommended) Spanner flat on 7-16 coupling nut Spanner flat on 4.3-10 coupling nut Cable diameter, jacket Tensile strength Recommended hanger spacing Minimum bend radius single Minimum bend radius repeated *Bending starts behind connector incl. the kink protection 25 to 30 Nm 5 to 8 Nm 32 mm 22 mm 13.5 mm typ. 700 N 0.8 m 25 mm* 35 mm*							
Environmental Data Operation temperature range Installation temperature range Degree of protection RoHS -40 °C to +80 °C -25 °C to +60 °C IEC 60529, IP68 1 bar for 1 h (mated) compliant							
While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.							
Draft		Date		Approved		Date	
M. Wimmer		05.09.2014		A. Gasteiger		28.02.2017	
Rev.		Engineering change number		Name		Date	
c00		17-0269		M_Buchholz		15.02.2017	
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
						Page 2 / 2	