Type:Multi-fole GrommetCables per Grommet:2 (two)Dimmensions:2 (two)Dimmensions:56.00 mm [2.204 in]Height:56.00 mm [2.204 in]Hole Shape:RoundCable Hole size:28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material SpecificationsCompatible Rosenberger Hardware	$ \begin{array}{c} & $	Technica	I Data Sheet	Rosenberger Site Solutions
When installed property, this product meets the requirements for installation in high Risk PM Zones, For use in High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, for use in High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, for use in High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, for use in High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, this product must be used in conjunction with other High Risk PM Zones, this product should only be performed to the suproved products. Nulli-hole Grommet 2 (two) Dimmensions: High Risk PM Zones, For use R Sp. Son mn [1.128 in Structions for this product should only be performed installation in sperformed. The manufacture or supplier of this product should be read throug before the results of improper or unsafe installation installation is performed. The manufacture or supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation is performed. The manufacture or supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation is performed. The manufacture or supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation is performed. The manufacture or supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation is performed. The manufacture or supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation is performed. The manufacture or supplier of this product discla	With hole of the product meets the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation in High Risk PIM Zones, the requirements for installation is the used in conjunction with other High Risk PIM Zones, the requirements for installation is the specific diverse in the requirements for installation is the specific diverse in the requirement is a specific d	1- 5/8" Han	ger Grommet	CX689-2810
Hanger Grommet for one 28.65 mm cable and one 9.5 mm fiber. Suitable for 1-5/8" Hangers and 1-5/8" Double Clamps. When installed properly, this product meets the requirements for installation in High Risk PIM Zones. For use in High Risk PIM Zones, this product must be used in conjunction with other High Risk PIM Zones, this product set used in conjunction with other High Risk PIM Zones, this product set used in conjunction with other High Risk PIM Zones, this product set used in conjunction with other High Risk PIM Zones, this product set used in conjunction with other High Risk PIM Zones, this product set used in conjunction with other High Risk PIM Zones, this product set used in conjunction with other High Risk PIM Zones, this product should only be performed. The manufacture of this product should be read throug before installation is performed. The manufacture of this product should be read througe before installation is performed. The manufacture of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice. Yape: Round Cable Hole size: 28.65 mm 8 9.50 mm [1.128 in 8 0.374 in] Material Specifications 8.0.374 in]	Hanger Grommet for one 28.65 mm cable and one 9.5 mm fiber. Suitable for 1-5/8" Hangers and 1-5/8" Double Clamps. When installed properly, this product meets the requirements for installation in High Risk PIM Zones. For use in High Risk PIM Zones, this product must be used in conjunction with other High Risk PIM Zones, this product must be used in conjunction with other High Risk PIM Zones, this product must be used in conjunction with other High Risk PIM Zones, this product should only be performed. Yupe: Multi-hole Grommet Cables per Grommet: 2 (two) Dimmensions: Height: Height: 56.00 mm [2.204 in] Hole Shape: Round 28.65 mm & 9.50 mm [1.128 in Cable Hole size: 28.65 mm & 9.50 mm [1.128 in Material Type: Rubber AsTM-1148-07a Unaffected by ozone, sunlight, aging or hot and cold weather. Standards: ASTM-1148-07a Waterial Type: Rubber Astandards: ASTM-1148-07a Unaffected by ozone, sunlight, aging or hot and cold weather. Folse 'Snap-Stack Hanger: TH415-U158 1-5/8'' Slowers Hanger: TH415-U158 1-5/8'' Slowers Hanger: TH428-S158 1-5/8'' Slowers Hanger: TH428-S158 1-5/8''' Slowers Hanger: TH428-S158 1-5/8''''''''''''''''''''''''''''''''''''			
Type:Multi-fole GrommetCables per Grommet:2 (two)Dimmensions:2 (two)Height:56.00 mm [2.204 in]Hole Shape:RoundCable Hole size:28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material SpecificationsCompatible Rosenberger Hardware	Type.Induction of GrommetCables per Grommet:2 (two)Dimmensions:2 (two)Height:56.00 mm [2.204 in]Hole Shape:Round28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material Specifications28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material Type:RubberMaterial Type:RubberStandards:ASTM-1148-07a Unaffected by ozone, sunlight, 	Suitable for 1-5/8" Hangers a When installed properly, this prinstallation in High Risk PIM Zou this product must be used in co Zone approved products. All dimensions are in mm.	and 1-5/8" Double Clamps. oduct meets the requirements for nes. For use in High Risk PIM Zones,	Note
Cables per Grommet:2 (two)instructions for this product should be read thoroug before installation is performed. The manufacturer a supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Dimmensions:56.00 mm [2.204 in]supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Height:56.00 mm [2.204 in]supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Cable Hole size:28.65 mm & 9.50 mm [1.128 in & 0.374 in]Compatible Rosenberger Hardware	Cables per Grommet:2 (two)instructions for this product should be read thorough before installation is performed. The manufacturer ar supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Height:56.00 mm [2.204 in]supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Height:56.00 mm [2.204 in]supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Hole Shape:Round28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material SpecificationsRubber1.5/8" Universal Hanger: TH415-U158 1-5/8" Snap-Stack Hanger: TH428-S158 1-5/8" Snap-Stack Hanger: TH428-S158 1-5/8" SIC Clamp: CX-SIC4-158Standards:ASTM-1148-07a Unaffected by ozone, sunlight, aging or hot and cold weather. RoHS Compliant10 pcs	Туре:	Multi-hole Grommet	Installation of this product should only be performed b
Dimmensions:before installation is performed. The manufacture a supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Height:56.00 mm [2.204 in]Hole Shape:RoundCable Hole size:28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material SpecificationsCompatible Rosenberger Hardware	Dimmensions:before installation is performed. The manufacturer are supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.Height:56.00 mm [2.204 in]Hole Shape:RoundCable Hole size:28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material Specifications28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material Specifications	••	2 (two)	trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly
Height S0:00 min [2:204 m] Hole Shape: Round 28.65 mm & 9.50 mm [1.128 in Cable Hole size: & 0.374 in] Material Specifications Compatible Rosenberger Hardware	Height.Soloo him [2.204 m]responsibility for the results of improper or unsafe installation practice.Hole Shape:Round 28.65 mm & 9.50 mm [1.128 in & 0.374 in]responsibility for the results of improper or unsafe 	Dimmensions:		before installation is performed. The manufacturer and
Hole Shape: Round installation practice. 28.65 mm & 9.50 mm [1.128 in 28.65 mm & 9.50 mm [1.128 in Cable Hole size: & 0.374 in] Material Specifications Compatible Rosenberger Hardware	Hole Shape:RoundCable Hole size:28.65 mm & 9.50 mm [1.128 in & 0.374 in]Material SpecificationsRubberMaterial Type:RubberMaterial Standards:ASTM-1148-07a Unaffected by ozone, sunlight, aging or hot and cold weather. ROHS CompliantPackaging Packaging quantity:10 pcs	Height:	56.00 mm [2.204 in]	
Cable Hole size: & 0.374 in] Material Specifications Compatible Rosenberger Hardware	Cable Hole size:& 0.374 in]Material SpecificationsCompatible Rosenberger HardwareMaterial Type:RubberMaterial Type:RubberStandards:ASTM-1148-07a Unaffected by ozone, sunlight, aging or hot and cold weather. ROHS Compliant1-5/8" Universal Hanger: TH415-U158 1-5/8" Snap-Stack Hanger: TH428-S158 1-5/8" Snap-Stack Hanger: TH497-DC158 1-5/8" SIC Clamp: CX-SIC4-158Packaging10 pcs	Hole Shape:		
1 E/0" Universal Manager TM445 1450	Material Type:Rubber1-5/8" Snap-Stack Hanger: TH428-S158ASTM-1148-07a1-5/8" Double Clamp: TH497-DC158Standards:Unaffected by ozone, sunlight, aging or hot and cold weather. ROHS Compliant1-5/8" SIC Clamp: CX-SIC4-158Packaging10 pcs		28.65 mm & 9.50 mm [1.128 in & 0.374 in]	Compatible Rosenberger Hardware
Material Types	ASTM-1148-07a 1-5/8" Double Clamp: TH497-DC158 Standards: Unaffected by ozone, sunlight, aging or hot and cold weather. RoHS Compliant 1-5/8" SIC Clamp: CX-SIC4-158 Packaging 10 pcs	Material Type:	Rubber	1-5/8" Snap-Stack Hanger: TH428-S158 1-5/8" Double Clamp: TH497-DC158
ASTM-1148-07a 1-5/8" Double Clamp: TH497-DC158 Unaffected by ozone, sunlight, aging or hot and cold weather.	Packaging Packaging quantity: 10 pcs	Standards:	Unaffected by ozone, sunlight, aging or hot and cold weather.	
		Packaging		
			10 pcs	
Weight Der Deskage 1.09 kg [2.4 lb]		vveigni Per Package	1.00 KY [2.4 ID]	

Ver: 201113.NR.v1.0