




Function Description

This part is a coaxial cable assembly for telecommunication equipment. It consists of 1/2" flexible coaxial cable with PE jacket, two 7/16 male connectors and two Rosenberger Jumper Boots for additional protection of the connector. The assembly is waterproof in mated condition and UV protected.

Available Variants

The assembly is available in lengths from 0.5 m to 10 m in intervals of 0.5 m. Different feet length are available on request.

Assembly Parts

Connector	7-16 male connectors plated with white bronze
Cable	S-Link 1/2"R, PE jacket
Marking 1	Direct print onto the cable or one wrapping label Marking includes manufacturer, part nr. & batch no.
Marking 2	Direct print onto the cable or on wrapping label Marking includes "Rosenberger factory made" Position in the middle of the cable
Bend Protection	molding material PE compound
Protection Boot	self-lubricating Silicone

Technical Data Sheet

1/2" JUMPER

7-16 MALE / 7-16 MALE

SLJ12RPW-60M60M-X-00

Electrical Data

Impedance	50 Ω
Frequency	DC to 2.7 GHz
Return loss	
DC – 1 GHz	≥ 32 dB
1 – 2.2 GHz	≥ 30 dB
2.2 – 2.7 GHz	≥ 28 dB
Insertion loss typ.	
DC – 1 GHz	≤ 0.08 dB/m (cable) + 0.01 dB * √f (GHz)
1 – 2.2 GHz	≤ 0.13 dB/m (cable) + 0.01 dB * √f (GHz)
2.2 – 2.7 GHz	≤ 0.15 dB/m (cable) + 0.01 dB * √f (GHz)
Intermodulation (3rd order @ 2 x 20 W)	typ. max.
	≤ -120 dBm ≤ -117 dBm
Relative Velocity of Propagation	88 %
DC breakdown voltage	2500 V

Mechanical Data

Coupling torque (recommended)	25 to 30 Nm
Spanner flat on coupling nut	32 mm
Cable diameter, jacket	16 mm typ.
Tensile strength	1100 N
Recommended hanger spacing	0.8 m
Minimum bend radius single	70 mm*
Minimum bend radius repeated	125 mm*
*Bending starts behind connector incl. the kink protection	

Environmental Data

Operation temperature range	-40 °C to +85 °C
Installation temperature range	-25 °C to +60 °C
Degree of protection	IEC 60529, IP68 1 bar for 1 h (mated)
RoHS	compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Wimmer	18.08.2015	F. Fraunhofer	18.08.2015	a00	15-s322	M. Wimmer	18.08.2015

Corporate Headquarters
Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O. Box 1260 D-84526 Tittmoning Germany
Tel. +49 8684 18-0

Rosenberger Site Solutions, LLC
P.O. Box 4268, Lake Charles, LA 70606
Ph.337.598.5250 Fax: 337.598.5290 rlss@rlss.us
www.RosenbergerOnline.us

Page
2 of 2